

## 180 160 140 Typical DAM, -40 C Typical DAM, 23 C 120 Typical DAM, 65 C Typical DAM, 121 C Stress - MPa 100 80 60 40 20 0 0.02 0.04 0.06 0.08 0 0.1 0.12 0.14 Strain - mm/mm

## RTP 205 H Tensile Stress/Strain (Molded Specimen Data)

No information supplied by RTP Company constitutes a warranty regarding product performance or use. Any information regarding performance or use is only offered as suggestion for investigation for use, based upon RTP Company or other customer experience. RTP Company makes no warranties, expressed or implied, concerning the suitability or fitness of any of its products for any particular purpose. It is the responsibility of the customer to determine that the product is safe, lawful and technically suitable for the intended use. The disclosure of information herein is not a license to operate under, or a recommendation to infringe any patents.



## 140 120 100 80 Stress - MPa 60 Molded Tensile Bars Approximate Longitudinal Orientation Behavior 40 Approximate Transverse **Orientation Behavior** 20 0 0.01 0.015 0.02 0.025 0 0.005 0.03 0.035 0.04 Strain - mm/mm

RTP 205 H Design Data (23 Degrees C)

No information supplied by RTP Company constitutes a warranty regarding product performance or use. Any information regarding performance or use is only offered as suggestion for investigation for use, based upon RTP Company or other customer experience. RTP Company makes no warranties, expressed or implied, concerning the suitability or fitness of any of its products for any particular purpose. It is the responsibility of the customer to determine that the product is safe, lawful and technically suitable for the intended use. The disclosure of information herein is not a license to operate under, or a recommendation to infringe any patents.